Fastmark M10XPd

Easy Implementation for Fast, Powerful Thermal Printing



PAL®: The AMT Datasouth Difference

Implementation is made easy with our plug and play capability - saving the IT team time and effort. In addition to popular emulations, our proprietary PAL® programming language resides in the smart printer allowing us to load an app that will accept your data stream and convert, format and print to fit your organization's requirements, including both linear and 2D barcodes. You can unplug any existing printer and replace it with the Fastmark® M10XPd. And, ongoing service and support, including future changes to the PAL® app, if needed, are available for the life of the printer.

- Easy to use touchscreen interface
- Print speeds up to 14 ips
- · Highest quality barcodes
- 203 and 300 dpi models available
- Our powerful and versatile "PAL"
- Zebra and other popular emulations





The M10XPd is ready for loading custom PAL® applications



PRINTER SPECIFICATIONS INCLUDE:

Printer Model Fastmark M10XPd

Resolution 203, 300 dpi

Command Set PAL Plus, Eltron, Zebra, Datamax

Printing Method Direct Thermal/Thermal Transfer

Print Speed Up to 14 ips – 203 dpi

Up to 12 ips – 300 dpi

Max Print Width 4.09 inches

Media Width 0.79" - 4.5"

Max Length 1000 inches – 203 dpi

450 inches - 300 dpi

Media Outside

Diameter 8.0

Optional: Full roll internal rewinder

Media Thickness 2.36 - 11.0 mil

Dimension (W) 10.9" x (D) 19.8"x (H) 12.8" or

(W) 10.9" x (D) 19.8" x (H) 16.2"

(Internal Rewind Option)

Remote Printer

Management SOTI Connect Compatible: enables users to

manage and maintain a fleet of barcode printers from the central dashboard and benefit from the reduced cost and complexity

of managing a myriad of IoT devices.

Weight 34 lbs or

41.7 lbs (Internal Rewind Option)

Display Touch Color RTS

Sensors Gap transmissive, black bar reflective

Memory 256 MB SDRAM

512 MB Flash

SD Flash Card for memory expansion

Processor 32-bit

Interfaces RS-232, USB, USB HOST (2),

Ethernet

Optional: GPIO, Bluetooth, WiFi 802.11 b/g/n (slot adapter)

Barcodes Linear and 2D

Ribbon Core 1"

Ribbon Outside

Diameter 3.5

Ink coated inside/outside

Cutter User Option

Real Time Clock Standard

Limited Warranty Printer: 2 years

Print Head: 1 year

Agency UL, UL c, CE, TUV, FCC, Energy Star



Identification Systems Group www.IdentificationSystemsGroup.com info@IdentificationSystemsGroup.com

