DATACARD® CD880" SERIES CARD PRINTER



The CD880 series card printer provides exceptional enterpriseclass desktop card printers — built for outstanding speed, printing quality, modularity, flexibility and reliable performance.

The best value in enterprise-class desktop card printing

The Datacard® CD880™ series card printer efficiently produces great-looking ID cards in less time than any other comparable desktop printer. It's engineered and built to handle the higher volumes and requirements of state and local government, corporate, commercial and educational card issuance. When your application demands speed, performance and reliability in a compact and efficient unit, the CD880 card printer is the ideal choice.

A card production powerhouse fueled by innovation

Industry-leading print speeds. The CD880 series card printer dramatically improves your card issuance throughput with printing speeds that rival the fastest card printers in its class.

Industry-leading image quality. Reproduce intricate graphics such as state seals and school emblems with the CD880 series printer's enhanced print modes. Resolutions up to 300 x 1200 dpi — an industry first — mean that fine text, 2D bar codes and complex two-byte character sets print sharp and bleed-free. Exclusive TrueMatch™ printing technology delivers vibrant colors that more closely match the colors on your screen.

Reliable operation. The CD880 series printer withstands the daily demands of enterprise-level card issuance. Industry-exclusive TruePick™ card handling virtually eliminates jams by accurately picking cards, standard or thin, with no adjustments.

Best value today and tomorrow. Rest assured that the CD880 series printer investment you make now will continue to pay off in the future. Modular design lets you field upgrade your CD880 series printers with different encoders, an inline lamination module option and features as your card issuance needs change.











MAKE THE CD880™ SERIES PRINTER PART OF YOUR TOTAL CARD ISSUANCE SOLUTION

A long pedigree of experience and innovation guided the development of the Datacard® CD880™ series card printer. We have more than 45 years of experience building card issuance systems, including more than 200,000 desktop systems. More than 400 government programs in 100 countries trust Datacard systems for their card issuance. So, we know the demands of your enterprise environment: Higher volumes. Extended production runs. Complex applications. More on-card technology. Greater security. All of these things factored into the design of the CD880 series printer. You not only get a desktop card printer that's compact and easy to use, you get an enterprise-class machine that's ready to take on your application.

FITS WHERE MOST CARD PRINTERS DON'T

- State and local government: Datacard printers are the choice for hundreds of state and local government card issuance programs. The CD880 series card printer's compact size and simple operation make it a great choice for a wide range of government applications, from transit passes to photo IDs for assistance program recipients.
- Corporate: Secure identification is the front-line defense for protecting people and assets. The CD880 series card printer can produce a wide variety of employee, contractor and visitor badges, plus time and attendance cards and access control cards to secure facilities and parking.
- Education: Keep student registration lines moving with the reliable, high-speed CD880 series card printer. Use it anywhere for on-the-spot issuance of multi-purpose campus cards, staff and student photo IDs, and access cards for libraries, residence halls and food services.

WORKS ON YOUR NETWORK

Your IT department will have an easy time adding the CD880 series card printer to your organization's network. It meets IT expectations for networked devices with standards-compliant Ethernet and USB connectivity. An internal print server eliminates the need for an external network box. IT administrators can keep your CD880 series printer up and running from anywhere using remote management and diagnostics. There's also a rich set of software tools for easily integrating the CD880 series printer into sophisticated, custom card issuance applications.

ENTERPRISE DOESN'T MEAN COMPLICATED

The CD880 series card printer maximizes your team's productivity by minimizing the time they need to learn and operate it. Printer controls and both the input and output card hoppers are conveniently up front for easy access. The reloadable supply cartridges simply load into the printer and laminator. Operation is a breeze. Intuitive icons and messages on the soft-touch LCD control panel guide you through printer operation, so you're never left wondering what to do next.

One great printer, dozens of great innovations

Years of development and numerous customer input sessions have gone into the creation of the CD880 series card printer. It's packed with industry-leading innovations and features, such as:

- Automatic 100-card input hopper with exception card slot, optional 200-input hopper
- 25-card output hopper standard with optional 100-card output hopper
- Optional laminator with unique card debower, tactile impression feature
- Optional, field-upgradable smart card and magnetic stripe encoding modules
- Optional, field-upgradable smart card and magnetic stripe encoding modules

- Two-sided or one-sided card printer models (factory option or field upgradeable)
- Color and UV, or monochrome printing in the same unit
- Reloadable supply cartridges with drop-in cleaning roller
- Intuitive LCD panel with soft-touch controls and soft-power switch

- Ethernet and USB connectivity standard on all CD880 printer models
- Advanced printer driver; support for third-party application development



Datacard CD880 Card Printer with inline lamination module

- The Datacard CD880 series card printer is an ideal choice for applications such as:
- Employee, contractor and visitor IDs
- Student and faculty ID cards
- Government photo IDs
- Casino frequent player cards
- Photo IDs for government assistance programs



Datacard CD880 Series Card Printer



ENHANCED PRINTING

The CD880 series card printer solves the problem of printing fine text and intricate graphics onto plastic cards. With the 300 x 1200 dpi resolution advantage of the CD880 series printer, you can print 6-point text, 2D bar codes and complex two-byte character sets with the confidence that they will all be sharp, legible and bleed-free.

STRONGER SECURITY

With the CD880 series card printer with inline lamination module, you can add a tactile impression for enhanced security and branding.

Engineered for enterprise-class ID card issuance

With its industry-leading speed, print quality and reliable performance, the Datacard® CD880™ series card printer is the new workhorse for enterprise-class card issuance. And, as these specs show, the CD880 series card printer is engineered to fit your most demanding applications. You've read about it, now see a demo. Ask us today about the CD880 series card printer.

CD880 Printer Standard Features and Specifications

Field upgradeable options: Single-wire contact/contactless all-in-one encoder (read/write) for MIFARE, ISO7816, ISO14443 A/B ISO Felica. DESFire ICLASS by HID, read/write encoder or read-only ICLASS SEOS by HID, read/write or read-only encounter PC Prox by HID, read-only Third-party OEM smart card option-ready (for contactless readers only – encoder not included) DUALI Single Wire Contact/Contactless Encoder, ISO 7816, ISO 14443, Mifare, Desfire & Felica OpenCard Factory option only; Supports one- and two-sided printing; Full-color and monochrome printing Front exception card slot supported; Supports legacy OpenCard formats; Ethernet or USB Two-sided printing Factory option or field upgradeable End-user upgradeable Extended 100-card output hopper (available for single-hopper); Extended 200-card input hopper and	Print technology	Direct-to-card dye-sublimation/resin thermal transfer		
High-quality mode: 300 x 600 dots per inch; enhanced text, bar code and graphics printing 256 shades per color panel Print speed Full-color printing: Up to 220 cards per hour printing cards on one side (WMCKT*) Up to 165 cards per hour printing cards on one side (WMCKT*) Monochrome printing: Up to 1000 cards per hour printing cards on one side (Black HQ*) Card capacity Automatic feed: 100-card input for 0.030 in. (0.76 mm) cards; 25-card output standard Front exception card slot Separate reject location and holding tray (10-card capacity) Input hopper empty detection One-sided printing: L 71.2 in. x W 8.8 in. x H 8.8 in. (44.2 cm x 22.4 cm x 22.4 cm) Two-sided printing: L 21.2 in. x W 8.8 in. x H 8.8 in. (53.8 cm x 22.4 cm) 25 cmpartment multi-hopper: L 27.5 in x W 16.5 in. x H 14.5 in. (69.9 cm x 41.9 cm x 36.8 cm) Weight One-sided printing: 10.0 lbs (4.1 kg) (depending on options) Six-compartment multi-hopper: L37.5 in x W 16.5 in. x H 14.5 in. (69.9 cm x 41.9 cm x 36.8 cm) Wight Did by the printing: 10.0 lbs (54.4 kg) (depending on options) Six-compartment multi-hopper: 33.0 lbs (15.0 kg) Connectivity Bidirectional USB 2.0 high speed; Ethernet 10 Base-T/100-Base-TX (with activity light) Warranties 36-month standard depot warranty; 36-month printhead warranty (no pass restrictions) CD880 Printer Options Magnetic stripe encoding ISO 7811 thee-track option (high- and low-coercivity) JIS Type I single-track option Support for standard and custom data formats Hopper 200-card input hopper Laminator Single- or dual-sided lamination Up to 185 cards per hour (ront side YMCK-K ribbon, back side K with front side lamination Up to 185 cards per hour (ront side YMCK-K ribbon, back side K with front side lamination Up to 200 cards per hour (ront side YMCK-K ribbon, back side K with front side lamination Up to 200 cards per hour (ront side YMCK-K ribbon with front side lamination Up to 185 cards per hour (ront side YMCK-K ribbon with front side lamination Up to 200 cards per hour (ront side yminter and laminati	Print capabilities	Full-color and UV, or monochrome printing capability in the same printer Alphanumeric text, logos and digitized signatures; 1D/2D bar code images		
Print speed Full-color printing: Up to 1220 cards per hour printing cards on one side (YMCKT*) Up to 165 cards per hour printing cards on two sides (YMCKT-K*) Monochrome printing: Up to 1.000 cards per hour printing cards on two sides (KMCKT-K*) Monochrome printing: Up to 1.000 cards per hour printing cards on one side (Black HQ*) Card capacity Automatic feed: 100-card input for 0.030 in. (0.76 mm) cards; 25-card output standard Front exception card slot Separate reject location and holding tray (10-card capacity) Input hopper empty detection Physical dimensions One-sided printing: L 17.4 in. x W 8.8 in. x H 8.8 in. (44.2 cm x 22.4 cm x 22.4 cm) Two-sided printing: L 21.2 in. x W 8.8 in. x H 8.8 in. (44.2 cm x 22.4 cm x 22.4 cm) Tive-sided printing: L 17.4 in. x W 8.8 in. x H 8.8 in. (44.2 cm x 22.4 cm x 22.4 cm) Two-sided printing: 12.1 in. x W 8.8 in. x H 8.8 in. (44.2 cm x 22.4 cm x 22.4 cm) Two-sided printing: 12.0 lbs (5.4 kg) (depending on options) Two-sided printing: 12.0 lbs (5.4 kg) (depending on options) Two-sided printing: 12.0 lbs (5.4 kg) (depending on options) Six-compartment multi-hopper: 23.0 lbs (15.0 kg) Connectivity Bidirectional USB 2.0 high speed; Ethernet 10 Base-T/100-Base-TX (with activity light) Warranties 36-month standard depot warranty; 36-month printhead warranty (no pass restrictions) CD880 Printer Options Magnetic stripe encoding ISO 78II three-track option (high- and low-coercivity) JIS Type II single-track option Support for standard and custom data formats Hopper 200-card input hopper Laminator Single- or dual-sided lamination Up to 200 cards per hour (not side YMCK-K ribbon, back side K with front side lamination Up to 200 cards per hour (side ymit and lamination with factile) YMCK Up to 200 cards per hour (side ymit and lamination with factile) YMCK-K Smart card personalization Factory option: DUALI Single Wire Contact/Contactless Encoder, ISO 78I6, ISO 14443, Mifare, Desfire & Felica Two-wire contact/contactless all-in-one encoder (read/write) for MIFARE/DES	Print resolution	High-quality mode:	300 x 600 dots per inch; enhanced text, bar code and graphics printing	
Up to 165 cards per hour printing: Cards on two sides (YMCKT-K*) Monochrome printing: Up to 1,000 cards per hour printing cards on one side (Black HQ*) Card capacity Automatic feed: 100-card input for 0,030 in. (0,76 mm) cards; 25-card output standard Front exception card slot Separate reject location and holding tray (10-card capacity) Input hopper empty detection Physical dimensions One-sided printing: L 17.4 in. x W 8.8 in. x H 8.8 in. (44.2 cm x 22.4 cm x 22.4 cm) Two-sided printing: L 17.2 in. x W 8.8 in. x H 8.8 in. (53.8 cm x 22.4 cm x 22.4 cm) Six-compartment multi-hopper: L 72.5 in x W 16.5 in. x H 14.5 in. (69.9 cm x 41.9 cm x 36.8 cm) Weight One-sided printing: 9.0 lbs (41.1kg) (depending on options) Two-sided printing: 12.0 lbs (54.1kg) (depending on options) Six-compartment multi-hopper: L 72.5 in x W 16.5 in. x H 14.5 in. (69.9 cm x 41.9 cm x 36.8 cm) Weight One-sided printing: 12.0 lbs (54.1kg) (depending on options) Six-compartment multi-hopper: L 72.5 in x W 16.5 in. x H 14.5 in. (69.9 cm x 41.9 cm x 36.8 cm) Warranties 36-month standard depot warranty; 36-month printhead warranty (no pass restrictions) CD880 Printer Options Magnetic stripe encoding Field upgradeable encoding Field upgradeable encoding JIS Type Il single-track option Support for standard and custom data formats Hopper 200-card input hopper Laminator Single- or dual-sided lamination Up to 200 cards per hour front side YMCK ribbon with front side lamination Up to 185 cards per hour front side YMCK ribbon with front side lamination Up to 200 cards per hour (two side print and lamination with Tactile) YMCK. Up to 200 cards per hour (two side print and lamination with Tactile) YMCK. Smart card personalization Factory option: - DUALI Single Wire Contact/Contactless Encoder, ISO 7816, ISO 14443, Mifare, Desfire & Felica Two-wire contact/contactless all-in-one encoder (read/write) for MIFARE/IDESFire, ISO7816, ISO14444 A/B - ISO Felica DESFire - ICLASS EVOS by HID, read/write or read-only encounter - PC Prox by HI		256 shades per color panel		
Card capacity Automatic feed: 100-card input for 0.030 in. (0.76 mm) cards; 25-card output standard Front exception card slot Separate reject location and holding tray (10-card capacity) Input hopper empty detection Physical dimensions One-sided printing: L 17.4 in. x W 8.8 in. x H 8.8 in. (44.2 cm x 22.4 cm x 22.4 cm) Two-sided printing: L 12.12 in. x W 8.8 in. x H 8.8 in. (53.8 cm x 22.4 cm x 22.4 cm) Six-compartment multi-hopper: L 27.5 in x W 16.5 in x H 14.5 in. (69.9 cm x 41.9 cm x 36.8 cm) Weight One-sided printing: 9.0 lbs (41 kg) (depending on options) Two-sided printing: 12.0 lbs (5.4 kg) (depending on options) Six-compartment multi-hopper: 33.0 lbs (15.0 kg) Connectivity Bidirectional USB 2.0 high speed: Ethernet 10 Base-T/100-Base-TX (with activity light) Warranties CD880 Printer Options Magnetic stripe encoding Field upgradeable ISO 7811 three-track option (high- and low-coercivity) JIS Type II single-track option Support for standard and custom data formats Hopper 200-card input hopper Laminator Single or dual-sided lamination Up to 185 cards per hour front side YMCK-ribbon with front side lamination up to 185 cards per hour front side YMCK-ribbon, back side K with front side lamination Up to 185 cards per hour front side YMCK-ribbon, back side K with front side lamination Up to 200 cards per hour (two sided print and lamination with Tactile) YMCK-K Up to 200 cards per hour (two sided printer and lamination with Tactile) YMCK-K Up to 200 cards per hour (two sided printer and lamination with Tactile) YMCK-K Smart card personalization Factory option: • DUALI Single Wire Contact/Contactless Encoder, ISO 7816, ISO 14443, Mifare, Desfire & Felica Two-wire contact/contactless all-in-one encoder (read/write) for MIFARE/IDESFire, ISO 7816, ISO 14443 A/B • ISO Felica, DESFire • ICLASS by HID, read-only • ICLASS SEOS by HID, read-only • Interparty OEM smart card option-ready (for contactless readers only - encoder not included) • DUALI Single Wire Contact/Contactless Encoder, ISO 7816, ISO	Print speed		Up to 165 cards per hour printing cards on two sides (YMCKT-K*)	
Two-sided printing: L 21.2 in. x W 8.8 in. x H 8.8 in. (53.8 cm x 22.4 cm x 22.4 cm) Six-compartment multi-hopper: L 27.5 in x W 16.5 in. x H 14.5 in. (69.9 cm x 41.9 cm x 36.8 cm) Weight One-sided printing: 9.0 lbs (41.8g) (depending on options) Two-sided printing: 12.0 lbs (54.8g) (depending on options) Six-compartment multi-hopper: 33.0 lbs (15.0 kg) Connectivity Bidirectional USB 2.0 high speed; Ethernet 10 Base-T/100-Base-TX (with activity light) Warranties 36-month standard depot warranty; 36-month printhead warranty (no pass restrictions) CD880 Printer Options Magnetic stripe encoding ISO 7811 three-track option (high- and low-coercivity) JIS Type II single-track option Support for standard and custom data formats Hopper 200-card input hopper Laminator Single- or dual-sided lamination Print, lamination and tactile Up to 210 cards per hour front side YMCK-r hibbon, back side K with front side lamination Up to 185 cards per hour front side YMCK-r hibbon, back side K with front side lamination Up to 200 cards per hour (one side print and lamination with Tactile) YMCK-g Smart card personalization Factory option: DUALI Single Wire Contact/Contactless Encoder, ISO 7816, ISO 14443, Mifare, Desfire & Felica Two-wire contact/contactless all-in-one encoder (read/write) for MIFARE/DESFire, ISO7816, ISO1444, Field upgradeable options: Single-wire contact/contactless all-in-one encoder (read/write) for MIFARE, ISO7816, ISO14443, Mifare, Desfire & Felica Two-wire contact/contactless all-in-one encoder (read/write) for MIFARE, ISO7816, ISO14443, Mifare, Desfire & Felica Type-Prox by HID, read/write encoder or read-only encounter PC Prox by HID, read/write encoder or read-only encounter PC Prox by HID, read/write encoder or read-only encounter PC Prox by HID, read/write encoder or read-only encounter PC Prox by HID, read/write encoder or read-only encounter PC Prox by HID, read/write encoder or read-only encounter PC Prox by HID, read/write encoder or read-only encounter PC Prox by HID, read/write enc	Card capacity	Front exception card slot Separate reject location and holding tray (10-card capacity)		
Two-sided printing: 12.0 lbs (5.4 kg) (depending on options) Six-compartment multi-hopper: 33.0 lbs (15.0 kg) Connectivity Bidirectional USB 2.0 high speed; Ethernet 10 Base-T/100-Base-TX (with activity light) 36-month standard depot warranty; 36-month printhead warranty (no pass restrictions) CD880 Printer Options Magnetic stripe encoding Field upgradeable ISO 7811 three-track option (high- and low-coercivity) JIS Type II single-track option Support for standard and custom data formats Hopper 200-card input hopper Laminator Single- or dual-sided lamination Print, lamination and tactile impression speed Up to 210 cards per hour front side YMCK ribbon with front side lamination Up to 185 cards per hour fone side print and lamination with Tactile) YMCK Up to 200 cards per hour one side print and lamination with Tactile) YMCK-K Smart card personalization Factory option: • DUALi Single Wire Contact/Contactless Encoder, ISO 7816, ISO 14443, Mifare, Desfire & Felica Two-wire contact/contactless all-in-one encoder (read/write) for MIFARE, ISO7816, ISO14443 A/B • ISO Felica. DESFire • ICLASS by HID, read/write encoder or read-only • ICLASS SEOS by HID, read/write encoder or read-only • ICLASS SEOS by HID, read/write or read-only • Third-party DEM smart card option-ready (for contactless readers only – encoder not included) • DUALi Single Wire Contact/Contactless Encoder, ISO 7816, ISO 14443, Mifare, Desfire & Felica OpenCard Factory option only; Supports one- and two-sided printing; Full-color and monochrome printing Front exception card slot supported; Supports legacy OpenCard formats; Ethernet or USB Two-sided printing Factory option or field upgradeable End-user upgradeable Extended 100-card output hopper (available for single-hopper); Extended 200-card input hopper and	Physical dimensions	Two-sided printing: L 21.2 in. x W 8.8 in. x H 8.8 in. (53.8 cm x 22.4 cm x 22.4 cm)		
Warranties 36-month standard depot warranty; 36-month printhead warranty (no pass restrictions) CD880 Printer Options Magnetic stripe	Weight	Two-sided printing: 12.0 lbs (5.4 kg) (depending on options)		
Magnetic stripe encoding Field upgradeable ISO 7811 three-track option (high- and low-coercivity) JIS Type II single-track option (support for standard and custom data formats Hopper 200-card input hopper Laminator Single- or dual-sided lamination Print, lamination Up to 210 cards per hour front side YMCK-ribbon with front side lamination Up to 185 cards per hour front side YMCK-ribbon, back side K with front side lamination Up to 200 cards per hour front side print and lamination with Tactile) YMCK Up to 200 cards per hour (two sided printer and lamination with Tactile) YMCK-K Smart card Factory option: DUALI Single Wire Contact/Contactless Encoder, ISO 7816, ISO 14443, Mifare, Desfire & Felica Two-wire contact/contactless all-in-one encoder (read/write) for MIFARE/DESFire, ISO7816, ISO14444 Field upgradeable options: Single-wire contact/contactless all-in-one encoder (read/write) for MIFARE, ISO7816, ISO14443 A/B 1SO Felica DESFire iCLASS' by HID, read/write encoder or read-only 1CLASS SEOS by HID, read/write or read-only encounter PC Prox by HID, read/write or read-only encounter PC Prox by HID, read-only 1Third-party OEM smart card option-ready (for contactless readers only – encoder not included) 1DUALI Single Wire Contact/Contactless Encoder, ISO 7816, ISO 14443, Mifare, Desfire & Felica OpenCard Factory option only; Supports one- and two-sided printing; Full-color and monochrome printing Front exception card slot supported; Supports legacy OpenCard formats; Ethernet or USB Two-sided printing Factory option or field upgradeable End-user upgradeable Extended 100-card output hopper (available for single-hopper); Extended 200-card input hopper and	Connectivity	Bidirectional USB 2.0 high speed; Ethernet 10 Base-T/100-Base-TX (with activity light)		
Magnetic stripe encoding Field upgradeable ISO 7811 three-track option (high- and low-coercivity) JIS Type II single-track option Support for standard and custom data formats Hopper 200-card input hopper Laminator Single- or dual-sided lamination Print, lamination and tactile Up to 210 cards per hour front side YMCK ribbon with front side lamination Up to 185 cards per hour front side YMCK-K ribbon, back side K with front side lamination Up to 200 cards per hour (one side print and lamination with Tactile) YMCK-K Smart card personalization Factory option: - DUALi Single Wire Contact/Contactless Encoder, ISO 7816, ISO 14443, Mifare, Desfire & Felica Two-wire contact/contactless all-in-one encoder (read/write) for MIFARE/DESFire, ISO7816, ISO14443 A/B iSIO PeliCa. DESFire - iCLASS' by HID, read/write encoder or read-only - iCLASS SEOS by HID, read/write or read-only encounter - PC Prox by HID, read/write or read-only encounter - PC Prox by HID, read/write or read-only encounter - PC Prox by HID, read-only - Third-party OEM smart card option-ready (for contactless readers only – encoder not included) - DUALi Single Wire Contact/Contactless Encoder, ISO 7816, ISO 14443, Mifare, Desfire & Felica OpenCard Factory option only; Supports one- and two-sided printing; Full-color and monochrome printing Front exception card slot supported; Supports legacy OpenCard formats; Ethernet or USB Two-sided printing Factory option or field upgradeable End-user upgradeable Extended 100-card output hopper (available for single-hopper); Extended 200-card input hopper and	Warranties	36-month standard dep	ot warranty; 36-month printhead warranty (no pass restrictions)	
encoding ISO 7811 three-track option (high- and low-coercivity) JIS Type II single-track option Support for standard and custom data formats Hopper 200-card input hopper Laminator Single- or dual-sided lamination Print, lamination and tactile Up to 210 cards per hour front side YMCK ribbon with front side lamination Up to 185 cards per hour front side YMCK-K ribbon, back side K with front side lamination Up to 200 cards per hour (one side print and lamination with Tactile) YMCK Up to 200 cards per hour (two sided printer and lamination with Tactile) YMCK-K Smart card personalization Factory option: **DUALI Single Wire Contact/Contactless Encoder, ISO 7816, ISO 14443, Mifare, Desfire & Felica Two-wire contact/contactless all-in-one encoder (read/write) for MIFARE/DESFire, ISO7816, ISO14443 Field upgradeable options: **Single-wire contact/contactless all-in-one encoder (read/write) for MIFARE, ISO7816, ISO14443 A/B **ISO FeliCa. DESFire** **CLASS 'by HID, read/write or read-only **CLASS SEOS by HID, read/write or read-only encounter* **PC Prox by HID, read/write or sead-only encounter* **PC Prox by H	CD880 Printer Options			
Description Single- or dual-sided lamination Print, lamination and tactile Up to 210 cards per hour front side YMCK-ribbon with front side lamination Up to 185 cards per hour front side YMCK-Kribbon, back side K with front side lamination Up to 200 cards per hour (one side print and lamination with Tactile) YMCK-K Up to 200 cards per hour (two sided printer and lamination with Tactile) YMCK-K Smart card personalization Factory option: DUALi Single Wire Contact/Contactless Encoder, ISO 7816, ISO 14443, Mifare, Desfire & Felica Two-wire contact/contactless all-in-one encoder (read/write) for MIFARE/DESFire, ISO7816, ISO14444. Field upgradeable options: Single-wire contact/contactless all-in-one encoder (read/write) for MIFARE, ISO7816, ISO14443 A/B ISO Felica. DESFire iCLASS by HID, read/write encoder or read-only iCLASS SEOS by HID, read/write or read-only encounter PC Prox by HID, read-only Third-party OEM smart card option-ready (for contactless readers only – encoder not included) DUALi Single Wire Contact/Contactless Encoder, ISO 7816, ISO 14443, Mifare, Desfire & Felica OpenCard Factory option only; Supports one- and two-sided printing; Full-color and monochrome printing Front exception card slot supported; Supports legacy OpenCard formats; Ethernet or USB Two-sided printing End-user upgradeable Extended 100-card output hopper (available for single-hopper); Extended 200-card input hopper and		ISO 7811 three-track option (high- and low-coercivity) JIS Type II single-track option		
Print, lamination and tactile Up to 210 cards per hour front side YMCK-ribbon with front side lamination Up to 185 cards per hour front side YMCK-ribbon, back side K with front side lamination Up to 200 cards per hour (one side print and lamination with Tactile) YMCK Up to 200 cards per hour (two sided printer and lamination with Tactile) YMCK-K Smart card personalization Factory option: • DUALi Single Wire Contact/Contactless Encoder, ISO 7816, ISO 14443, Mifare, Desfire & Felica Two-wire contact/contactless all-in-one encoder (read/write) for MIFARE/DESFire, ISO7816, ISO14443 A/B • ISO Felica. DESFire • iCLASS' by HID, read/write encoder or read-only • iCLASS SEOS by HID, read/write or read-only encounter • PC Prox by HID, read/write or read-only encounter • PC Prox by HID, read-only • Third-party OEM smart card option-ready (for contactless readers only – encoder not included) • DUALi Single Wire Contact/Contactless Encoder, ISO 7816, ISO 14443, Mifare, Desfire & Felica OpenCard Factory option only; Supports one- and two-sided printing; Full-color and monochrome printing Front exception card slot supported; Supports legacy OpenCard formats; Ethernet or USB Two-sided printing End-user upgradeable Extended 100-card output hopper (available for single-hopper); Extended 200-card input hopper and	Hopper	200-card input hopper		
and tactile impression speed Up to 185 cards per hour front side YMCK-K ribbon, back side K with front side lamination Up to 200 cards per hour (one side print and lamination with Tactile) YMCK-W Up to 200 cards per hour (two sided print and lamination with Tactile) YMCK-K Smart card personalization Factory option: • DUALi Single Wire Contact/Contactless Encoder, ISO 7816, ISO 14443, Mifare, Desfire & Felica Two-wire contact/contactless all-in-one encoder (read/write) for MIFARE/DESFire, ISO7816, ISO14443 A/B • ISO FeliCa. DESFire • iCLASS' by HID, read/write encoder or read-only • iCLASS SEOS by HID, read/write or read-only encounter • PC Prox by HID, read-only • Third-party OEM smart card option-ready (for contactless readers only – encoder not included) • DUALi Single Wire Contact/Contactless Encoder, ISO 7816, ISO 14443, Mifare, Desfire & Felica OpenCard Factory option only; Supports one- and two-sided printing; Full-color and monochrome printing Front exception card slot supported; Supports legacy OpenCard formats; Ethernet or USB Two-sided printing End-user upgradeable Extended 100-card output hopper (available for single-hopper); Extended 200-card input hopper and	Laminator	Single- or dual-sided lamination		
personalization • DUALi Single Wire Contact/Contactless Encoder, ISO 7816, ISO 14443, Mifare, Desfire & Felica Two-wire contact/contactless all-in-one encoder (read/write) for MIFARE/DESFire, ISO7816, ISO14443 A/B Field upgradeable options: • Single-wire contact/contactless all-in-one encoder (read/write) for MIFARE, ISO7816, ISO14443 A/B • ISO Felica. DESFire • iCLASS' by HID, read/write encoder or read-only • iCLASS SEOS by HID, read/write or read-only encounter • PC Prox by HID, read-only • Third-party OEM smart card option-ready (for contactless readers only – encoder not included) • DUALi Single Wire Contact/Contactless Encoder, ISO 7816, ISO 14443, Mifare, Desfire & Felica OpenCard Factory option only; Supports one- and two-sided printing; Full-color and monochrome printing Front exception card slot supported; Supports legacy OpenCard formats; Ethernet or USB Two-sided printing End-user upgradeable Extended 100-card output hopper (available for single-hopper); Extended 200-card input hopper and	and tactile	Up to 185 cards per hour front side YMCK-K ribbon, back side K with front side lamination Up to 200 cards per hour (one side print and lamination with Tactile) YMCK		
Front exception card slot supported; Supports legacy OpenCard formats; Ethernet or USB Two-sided printing Factory option or field upgradeable End-user upgradeable Extended 100-card output hopper (available for single-hopper); Extended 200-card input hopper and		DUALi Single Wire Contact/Contactless Encoder, ISO 7816, ISO 14443, Mifare, Desfire & Felica Two-wire contact/contactless all-in-one encoder (read/write) for MIFARE/DESFire, ISO7816, ISO14443, A/B Field upgradeable options: Single-wire contact/contactless all-in-one encoder (read/write) for MIFARE, ISO7816, ISO14443 A/B, ISO Felica. DESFire ICLASS by HID, read/write encoder or read-only ICLASS SEOS by HID, read/write or read-only encounter PC Prox by HID, read-only Third-party OEM smart card option-ready (for contactless readers only – encoder not included)		
End-user upgradeable Extended 100-card output hopper (available for single-hopper); Extended 200-card input hopper and	OpenCard			
	Two-sided printing	Factory option or field upgradeable		
printer	End-user upgradeable options	CD880 series printer with inline lamination module (available for single-hopper); KL-style security lock for		

^{*}Ribbon type and number of panels: Y=Yellow, M=Magenta, C=Cyan, K=Black, T=Inline Topcoat; HQ=High Quality



Identification Systems Group www.identificationsystemsgroup.com info@identificationsystemsgroup.com 888 864 6482



Corporate Headquarters

Phone: 888.437.9783 Fax: 952.975.0660 www.identisys.com 7630 Commerce Way Eden Prairie, MN 55344