OFFLINE MAILER SYSTEM







MS1000

THE EXCEPTIONAL VALUE FOR DIRECT CARD MAILING

The MS1000 card mailing system is a simple and affordable solution for entry-level stand-alone direct card mailing and fulfillment applications. It comes in a pre-packaged solution including reading station, card on carrier application, folding and envelope insertion.


Financial institutions and service bureaus can benefit of a compact and affordable solution for direct card mailing. Easy to operate, the MS1000 is a stand alone solution which comes with a pre-packaged software for easy installation and configuration offering a production speed up to 1000 cards per hour to fulfil the demanding needs of central issuance programs.

Financial cards, loyalty cards, healthcare cards and many others: the MS1000 can be configured to almost any application, capable of processing documents with up to four cards from two different hoppers from the tower feeder.

Once the cards and carriers have been securely matched, they are passed to the folding and insertion station. The unique folding system allows the carrier to be folded in C, V, or Z formats depending on the type of envelopes to be used.

The MS1000 is a highly durable system designed and build for performance, reliability and exceptional value.

Examples of carrier folded:









Matica Technologies AG Email: sales@maticatech.com



Identification Systems Group www.identificationsystemsgroup.com info@identificationsystemsgroup.com 888 864 6482

TECHNICAL SPECIFICATIONS

Production speed

Stand alone operation Up to 1000 cph

Card and consumables handling

Input hopper capacity: 600 cards for continuous production Reject card and carrier hoppers

Carrier paper handling

Carrier formats: A4 and US letter size Up to 100 g/m2 paper thickness 4 cards per carrier

Control console

Preconfigured, dedicated PC included using MaticardPro

Optional modules

Card data reading station Pre-folded document feeder Envelope sized document feeder

Software environment

MaticardPro for Windows® 8 and Windows 10 Diagnostic and setup software included PCI-DSS compliant software

Total dimensions

L (card side): 1800 mm (70.8") L (carrier side): 3750 mm (147.6") Depth: 550 mm (21.6") Height: 1400 mm (55.1")