Prima 8



Ultra high resolution printer for secure card issuance



Secure

The Magicard Prima 8 secures card issuance with a combination of inline and post-printing options. Ultraviolet (UV) images or text, printed inline, can be augmented with overlaminates for added durability and security – including standard and customised holographic options. A logical printer lock is fitted as standard.

Optional - 600 dpi high resolution printing

The ultra high resolution of 600dpi enables the printing of secure microtext and CJK characters down to a 1.3 point size. Fine-lines and detailed, secure graphical elements can be printed in photo quality, right over the edge of the card.



Trusted

High reliability and a market-leading 3 year warranty help ensure the Magicard Prima 8 is trusted worldwide for high-level secure card issuance projects – including drivers' licenses, secure travel passes and localised issuance of payment cards. It is FIPS 201 compliant and on the GSA Approved Product List.

Versatile

Ease of integration is facilitated by both USB and Ethernet interfaces, with magnetic stripe and a range of smart card encoding options all supported. An inline laminator can easily be added with connectivity enabled via infrared (IR).



Addicover PLUS

Free MagiCover Plus 3 year limited warranty and support*

Prima 8 is ideal for:

Enterprise, Government and Payments identity applications.

Prima 8

Printer highlights



Printer specifications

Print mode

300 dpi reverse-transfer printing technology. (Optional 600 dpi model available) Card security

Holographic laminates (requires lamination module) and UV film options

Encoding security options

Magnetic stripe encoding: HiCo and LoCo encoder ISO 7811

Smart card encoding: Contact chip, MIFARE®, DESFire® and iClass®. Others available. Warranty*

MagiCoverPlus 3 year limited warranty. Available in North America, EU and other selected

territories. Elsewhere 1 year minimum limited depot warranty. **Printer interfaces**

USB (Ver2.0) Full-Speed (12Mbps) and Hi-Speed (480Mbps) 10BASE-T/100BASE-TX Ethernet, both included as standard.

Driver compatibility

Windows 10 / 8.1 / 8 / 7 (SP1), both 32 / 64 bit Windows Server 2016 (64 bit) / 2012 (64 bit) / 2008 R2 (SP1) (64 bit) / 2003 R2 (SP2) (32 bit)

Card capacity

100 card input feeder and output stacker.

Weight

15.5kg (34.1lbs).

Dimensions

343mm width x 320mm height x 330mm length (13.5" width x 12.6" height x 13" length). Print speed

YMCK with transfer to card: 100 cards per hour single-sided.

Printhead

Simple field replaceable unit

Operating conditions

15°C to 30°C (59°F to 86°F); 35% to 70% non-condensing

Security features

A logical printer lock is fitted as standard

Consumables	

Dye film	
 Set of 5 YMCK dye films + 5 retransfer films, 1000 images each film. Colour dye film, YMCK, 1000 images Colour dye film, with black on reverse, YMCKK, 750 images Colour dye film, with UV panel on reverse, YMCK-UV, 750 images Colour dye film, with peel off panel on reverse, YMCK-PO, 750 images 	Prima 831 Prima 832 Prima 833 Prima 834 Prima 835
Retransfer film	
Retransfer film 1000 images.	Prima 436
Laminates	
Thin, 0.5 mil and 1 mil laminates available. Clear and holographic options.	
Card types / thickness	
CR80 PVC, ABS, PET, PVH, and Polycarbonate ISO blank cards, HiCo magnetic stripe and smart cards. 0.25mm to 1.0mm (0.010" to 0.040").	
Cleaning kit	

Cleaning kit Cleaning kit (10 cards) E9887

Variants

Prima 8 Duo

Magicard Prima 8 Duo 600 dpi; double-sided printer.

Variants (Mag, Smart or Smart Mag) - call for part numbers

Magnetic stripe card encoding, combi smart card encoding (contact chip, MIFARE®, DESFire®, iClass®). Other smart card encoders also available.

Options

Inline laminator

 Single-sided • Double-sided

Prima 451 Prima 452

Part No.

Card security options

For added durability and security - including

standard and customised holographic





UV printing

Ultraviolet film enables the printing of hidden photographs, logos, text or symbols that are only visible under UV light.



Magnetic stripe The Prima 8 can be specified with ISO standard 7811 compatible HiCo encoding of magnetic stripe cards.



Smart card encoding Smart card encoding options Contact chip, MIFARE®, DESFire®, iClass®.



options

*Warranty subject to the observance of specific conditions of use and maintenance, as well as the use of certified 'Original Magicard' dye films.

Magicard and Prima 8 are trademarks or registered trademarks of Magicard Ltd. All other trademarks, brand names, or product names belong to their respective holders The information contained in this document reflects the current state of design and we reserve the right to change the specification without notice or obligation.



Identification Systems Group

www.identificationsystemsgroup.com info@identificationsystemsgroup.com 888 864 6482

Issue: 1.01

