

ID MAX.U500i

UHF Vehicle Access Control Reader

- Combination of UHF Long Range Reader with integrated antenna and Access Controller
- Management of more than 4.000 access permissions
- Simultaneous monitoring of up to 2 lanes with read ranges of up to 10 m
- Non-volatile event memory, buffered real time clock and Teach-in-mode
- Anti Passback
- Integrated signal light (red/green)
- Secure Key Storage (Secure Element)
- Fast and easy mounting and installation
- PoE and USB interface



PART OF

myAXXESS**MAKE ACCESS CONTROL EASY**

Access control systems on buildings and parking areas should be as uncomplicated as possible. myAXXESS is the secure, powerful and economic solution for small and medium-sized projects. Both in a stand-alone systems and integrated into existing access solutions. As a RFID specialist, FEIG ELECTRONIC offers systems from a single source, consisting of:


- RFID hardware for short-range solutions (HF)
- RFID hardware for long-range solutions (UHF)
- Software myAXXESS Manager for administration of access authorizations
- Transponders for granting authorizations (HF chipcards and UHF wind shield transponders)

ID MAX.U500i is a compact UHF Vehicle Access Control Reader that combines a UHF Long Range Reader with integrated antenna, a signal light and an access controller in one device. The cabinet approach of this fail-safe solution ensures ease of installation and maintenance. Place of use is everywhere where vehicles should be granted permanent access to employee parking lots, driveways to companies, authorities or other closed facilities (Perimeter Protection).

For identification of a vehicle in connection with the ID MAX.U500i passive, maintenance-free UHF transponders are used, which can be stuck behind the windscreen of the vehicle. Supporting encryption techniques according to EPC Class 1 Gen 2 V2 specification like NXP UCODE DNA allows a secure authentication of detected transponders and prohibits access of transponders with cloned serial numbers.

With ID MAX.U500i more than 4.000 access permissions can be managed and up to 3.000 access control events can be stored. Each user can be assigned to additional temporal restrictions. Holidays and vacation days can be included, easily.

To monitor multiple lanes or the simultaneous checking of entry and exit, there are one antenna port and two digital outputs available, alternatively two relays as signal transmitter for barrier- or gate control units.



Loop detectors and motion detectors as useful accessories

Loop detectors and motion detectors as pulse for starting the identification process do not only ensure an energy efficient operation of ID MAX.U500i. They also guarantee that always the right barrier or door is opened when several lanes exist. For this ID MAX.U500i offers a digital input.

Suitable loop detectors and motion detectors are available from FEIG ELECTRONIC.



Perimeter Protection:
Fast and safe access to industrial plants etc.

Programming & Administration

Using the software myAXXESS Manager, user data and authorizations can be easily administrated and transferred to ID MAX.U500i by using a temporary connection. After this synchronization, the reader can run offline as a stand-alone device.

With the help of a USB stick, the event buffer as well as the entire configuration including the access authorization can be read out on the ID MAX.U500i. The simple "configuration cloning" allows this configuration to be conveniently copied to other devices by the same route.

The "Teach-In Mode" is used to teach the transponders to be accessed without the use of the software. If the reader is in this mode, all read transponders are automatically transferred to the access database.



Parking Management:
Comfortable access without waiting

Stand of informationen: March 2020

The information in this document is subject to change without notice and shall not be construed as a commitment. All brand names, trademarks or logos are property of their respective owners.



UHF Vehicle Access Control Reader with integrated antenna and signal light

Small and powerful UHF RAIN RFID Long Range Reader with integrated Access Controller for automatic vehicle identification (AVI).

Product details		ID MAX.U500i	
Mechanical Data			
Housing	Plastic (ASA-PC), Aluminium	Features	RAIN RFID
Dimensions	290 mm x 290 mm x 100 mm (11.4 x 11.4 x 3.9 inch)	Supported transponder types	EPC Class1 Gen2 EPC Class1 Gen2 V2 ISO 18000-6-C ISO 18000-63
Weight	2.800 g	Indicator	Signal light with red/green/blue 10 LEDs to indicate operation and antenna state
Mounting	VESA FDMI MIS-D 100 mm x 100 mm	Network Services	TCP/IP, DHCP
Protection Class	IP67	Other Features	Battery-assisted real-time clock, Supports encrypted transponder communication, Secure Key Storage, Config Cloning function
Colour	Anthracite, translucent		
Electrical Data		Environmental Conditions	
Power Supply	12...24 V DC ($\pm 10\%$), PoE+	Temperature range	
Power Consumption	typical 22 W	- Operation	-25° C up to 55° C
Operating Frequency		- Storage	-25° C up to 85° C
- Variant EU:	865 MHz up to 868 MHz		
- Variant FCC:	902 MHz up to 928 MHz	Humidity	5% to 95% (non-condensing)
Output Power		Vibration	EN 60068-2-6 10 Hz to 150 Hz: 0,075 mm / 1g
- Radiated (int. antenna)	max. 2 W ERP	Shock	EN 60068-2-27 Acceleration: 30 g
- Conducted (ext. ant.)	max. 1 W, configurable in steps of 100mW		
Antenna Connector for external antenna	1x R-TNC-Jack (50 Ω) (Reverse-TNC)	Applicable Standards	
RF-Diagnosis	RF-channel monitoring, Antenna SWR control, Internal Overheating Protection	Radio Regulation	
Outputs		- Europe	EN 302 208
- 2 Optocoupler	max. 24 V DC / 20 mA	- USA	FCC 47 CFR Part 15
- 2 Relays	max. 24 V DC / 1 A switching current, 2 A permanent current	- Canada	IC RSS-GEN, RSS-210
		- India	BIS IS 13252 Part 1
Inputs		EMC	EN 301 489
- 2 Optocoupler	max. 24 V DC / 20 mA	Safety	
Interfaces	Ethernet, USB (On-The-Go)	- Low Voltage	EN 62368
		- Human Exposure	EN 50364
		Others	RoHS, WEEE

Stand of informationen: March 2020

The information in this document is subject to change without notice and shall not be construed as a commitment.
All brand names, trademarks or logos are property of their respective owners.



IDENTIFICATION
SYSTEMS GROUP

Identification Systems Group
www.IdentificationSystemsGroup.com
info@isg-id.com 888.964.6482